

ELARIS INVERTER

MINI SPLIT SUBMITTAL DATA

MODEL NUMBERS:
EINV-24KEV-R32-XPRO18
EINV-24KCO-R32-XPRO18



T1, 220V, 60HZ
R32, INVERTER SPLIT AC



X PRO SERIES



GOLD FIN TREATED



3M COPPER PIPE



AHRI 18 SEER



WIFI READY



Specifications, performance ratings, and dimensions may change without prior notice and without liability. Improper installation, adjustment, modification, servicing, or maintenance may result in property damage or personal injury. All installation and servicing must be carried out by a qualified installer or authorized service professional.

PRESTIGE

Distributed By: **HVAC DISTRIBUTORS INC.**

ELARIS INVERTER

MINI SPLIT SUBMITTAL DATA

T1, 220V 60HZ R32
COOLING ONLY

KEY FEATURES



R32 Refrigerant



3M Copper Kit



Quiet Operation



Gold Fin Treated



AHRI CERTIFIED

18 SEER




High efficiency for lower energy consumption and cost savings.



SMART APP CONTROL VIA WIFI

Control temperature & modes from your smart device.



CONTACT US



sales@prestigehvac-us.com



www.prestigehvac.us

Distributed by:

PRESTIGE
HVAC DISTRIBUTORS INC.

Specifications, performance ratings, and dimensions may change without prior notice and without liability. Improper installation, adjustment, modification, servicing, or maintenance may result in property damage or personal injury. All installation and servicing must be carried out by a qualified installer or authorized service professional.

TECHNICAL SPECIFICATIONS_60Hz			
Type	Cooling Only		
Control Type	Remote		
Rated Cooling Capacity	Btu/h		23000(5120~24900)
EER for cooling	Btu/W		9.55 ; 2.80
SEER—AHRI			18
Moisture Removal	Liters/h		2.5
Pressure	High (DP)	MPa	4.5
	Low (SP)	MPa	1.9
Indoor noise level at cooling	High	dB(A)	49
	Med	dB(A)	46
	Low	dB(A)	40
Outdoor noise level		dB(A)	55
ELECTRICAL DATA			
Power Supply			208-230V~/60Hz/1P
Voltage Range	V		165~265
Rated Current	Cooling	A	11.4(1.5~12.0)
Rated Input	Cooling	W	2408(200~2750)
Max Current	Cooling	A	13
Max Power Input	Cooling	W	2900
REFRIGERATING SYSTEM			
Refrigerant			R32/800g
Compressor	Type		Rotary
	Model		C-1RZ140H3CBF
	MFG		SANYO
Evaporator			Φ7x2
Condenser			Φ5x2

ELARIS

FAN SYSTEM			
Indoor Air Circulation (Cooling)	m³/h		1300
Indoor Fan Type			Cross Flow
Indoor fan speed H/M/L	Cooling	rpm	1230/1170/1070/800/830
	Dry	rpm	1230
	Sleep	Rpm	800
Indoor fan motor output	W		60
Outdoor fan type			Propeller fan
Outdoor fan speed	Low (SP)	rpm	1000
Outdoor fan motor output	W		33
CONNECTIONS			
Connecting Pipe	Gas	Inches	1/2"
	Liquid	Inches	1/4"
Connecting Wiring	Size X Core Number		4 x0.75mm2
Drainage Pipe			O.D 16mm
OTHERS			
Net Dimensions (W X D X H)	Indoor	mm	1010x 321.5 x 220
	Outdoor	mm	853 x 349x 602
Net Weight	Indoor	Kg	11.5
	Outdoor	Kg	29
Packing dimensions (W X D X H)	Indoor	Mm	1080 x 390 x 297
	Outdoor	Mm	890 x 385 x 628
Gross weight with pipe	Indoor	Kg	15
	Outdoor	Kg	33